

AD-A066 888

NAVY UNDERWATER SOUND REFERENCE LAB ORLANDO FLA
HAZELTINE DT 287/BQA-8 HYDROPHONE SERIAL B70 DT 288/BQA-8 HYDRO--ETC(U)
FEB 66

F/G 17/1

UNCLASSIFIED

USRL-CALIBRATION-2405

NL

1 OF 1
AD A
066888



END
DATE
FILMED

6-79
DDC

AD A0 66888

DDC FILE COPY

CONFIDENTIAL
UNCLASSIFIED

SECRET
TOP SECRET

0

Calibration of

Baseline DT 257/ROA-3 Hydrophone Serial 177
DT 120/ROA-3 Hydrophone Serial A-150

Coolidge

11
15 JAN 1968

12
14 p.

DDC
RECEIVED
12 4 1968

12
14 p.

~~UNCLASSIFIED~~
~~CONFIDENTIAL~~

Department of the Navy, Office of Naval Research
USN UNDERWATER SOUND REFERENCE LABORATORY
P. O. Box 8337, Orlando, Florida 32806

EMR/hs
RP-2983
23 Feb 1966

CONFIDENTIAL - Group 4

CALIBRATION REPORT No. 2405

Subj: Hazeltine DT 287/BQA-8 hydrophone serial B70 and DT 288/BQA-8 hydrophone serial A-199; calibration of (U)

Ref: (a) BUSHIPS ltr C-9674 Ser 1622D-0905 of 13 Dec 1965
(b) USRL Calibration Report No. 2105 (RP-2658) of 28 Oct 1963

Encl: (1) Drawings USRL 41111 through 41113 and 20113

1. Calibration measurements on the subject hydrophones were requested by the Bureau of Ships in reference (a).

2. The hydrophones were hydrostatically tested to insure their capability for withstanding the desired pressure 3000 psig. This precaution is required because implosion of a hydrophone in the tube facility can damage the facility transducers and result in considerable expense and delay for repairs. Hydrophone DT 287/BQA-8 serial B70 failed at 2900 psig. The hydrophone filled with water when a hole developed about 1/8 in. from the metal clamping band. Hydrophone DT 288/BQA-8 serial A-199 received no apparent physical damage from 3000 psig pressure held for 30 minutes.

3. Drawing USRL 41111, enclosure (1), shows the results of free-field voltage sensitivity measurements made in the low-frequency tank in the frequency range 5 to 1000 Hz at the hydrostatic pressures 0 and 1000 psig and the temperature 22°C. Free-field voltage sensitivity measured in the tube facility in the range 100 Hz to 1.5 kHz at the pressures 0, 1000, and 3000 psig and the temperature 10°C is shown on drawing USRL 41112. The frequency ranges of the low-frequency tank and the tube facility can not be extended; they are characteristics of the systems. Except in the frequency range shown, there is no capability at the USRL for sensitivity measurements at pressures above 1000 psig.

4. Measurements in the anechoic tank consisted of free-field voltage sensitivity in the range 2 to 12 kHz at the pressures 0, 300, 500, 700, and 1000 psig and the temperature 8°C. The results are shown on drawing USRL 41113. Directivity measurements on a similar hydrophone were reported in reference (b); they were not made in the tests reported here. There is no capability for making directivity measurements at pressures above 1000 psig.

5. Orientation was as described for a cylindrical hydrophone on drawing USRL 20113. A cross marked on the hydrophone case served as the zero-degree reference.

This material contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Section 793 and 794, and the transmission or revelation of its contents in any manner to an unauthorized person is prohibited by law.

660305-C202

UNCLASSIFIED
~~CONFIDENTIAL~~
~~CONFIDENTIAL~~

UNCLASSIFIED

USRL Calibration Report No. 2405

23 Feb 1966

6. All measurements reported here were made in accordance with American Standard Procedures for Calibration of Electroacoustic Transducers, Particularly Those for Use in Water, Z24.24-1957. The USRL has adopted the international unit of frequency, the hertz (1 hertz = 1 Hz = 1 cps; 1 kilohertz = 1 kHz = 1 kc/sec).

Eva M. Raybun
EVA M. RAYBUN

Copy to:

BUSHIPS (Code 452E)(1)

→ (Code 1622D)(1)

(Code 1634C3)(1)

USL (Mr. W. C. Nordstrom)(1)

USRL (Code 200)(1)

ACCESSION for	
NTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
<i>Added on file</i>	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

UNCLASSIFIED

CONFIDENTIAL

UNDERWATER SOUND REFERENCE LABORATORY
P. O. Box 8337, Orlando, Florida

FREE-FIELD VOLTAGE SENSITIVITY

Hazeltine DT 288/BQA-8 Hydrophone

Serial A-199

Open-circuit crystal voltage

—— 0 psig before and after pressure
--- 1000 psig

Proj. No. **RP-2983**
Date: **Jan 1966**


Water temp: **22 °C**

MEASUREMENTS MADE IN AC-
CORDANCE WITH AMERICAN
STANDARD Z.24.24-1967

HYDROPHONE VOLTAGE COUPLING (in decibels of
voltage) is the difference between the open-circuit crystal voltage

1 psig - 114.4 dB
10 psig - 114.4 dB
50 psig - 114.4 dB
50-1000 psig - 114.4 dB

Decibels re one volt per microbar



END USRL-ORL-3960/6 (3-61)

CONFIDENTIAL END JAN

CONFIDENTIAL

Department of the Navy, Office of Naval Research
UNDERWATER SOUND REFERENCE LABORATORY
P. O. Box 8337, Orlando, Florida 32806

USRL No. 41112

Proj. No. RP-2983

Date: Jan 1966

FREE-FIELD VOLTAGE SENSITIVITY

Hazeltine DT 288/BQA-8 Hydrophone


Serial A-199

Open-circuit crystal voltage

——— 0 psig
- - - 1000 psig
- - - 3000 psig

Water temp: 10 °C

MEASUREMENTS MADE IN AC-
CORDANCE WITH AMERICAN
STANDARD Z.24.24-1957



END USRL ORL 2980/2 (2-51)

CONFIDENTIAL

CONFIDENTIAL

(Unclassified until 2025)

Department of the Navy, Office of Naval Research
UNDERWATER SOUND REFERENCE LABORATORY
P. O. Box 8337, Orlando, Florida

USRL No. 41113

Proj. No. RP-2983

Date: Feb 1966

FREE-FIELD VOLTAGE SENSITIVITY

Hazeltine DT 288/BQA-8 Hydrophone


Serial A-199

Open-circuit crystal voltage

—— 0 psig - - - - 1 000 psig
- - - - 300 psig - · - · - 0 psig after pressure
- · - · - 500 psig
· · · · · 700 psig

Water temp: 8 °C


MEASUREMENTS MADE IN AC-
CORDANCE WITH AMERICAN
STANDARD Z.24.24-1957



15 May 1958

COORDINATE SYSTEM FOR TRANSDUCER ORIENTATION

The left-handed coordinate system of the American Standard Procedures for Calibration of Electroacoustic Transducers Particularly Those for Use in Water, Z24.24-1957, is used. The transducer is fixed with respect to the coordinate system and has its acoustic center at the origin. The angle ϕ is equivalent to the azimuth angle in sonar operation.



PLACEMENT OF TRANSDUCER IN COORDINATE SYSTEM

Transducer Type	Transducer Orientation in Coordinate System
Point, or Spherical	Points on surface that coincide with the X and Z axes shall be specified.
Cylindrical, or Line	The axis of the cylinder or line shall coincide with the Z axis. A reference mark in the XZ plane and in the direction of the positive X axis will be specified.
Plane, or Piston	The plane or piston face shall be in the YZ plane with the X axis normal to the face at its acoustic center. A reference mark in the XZ plane and in the direction of the positive Z axis will be specified.
Other Configurations	Orientation shall be shown by sketch or description. This category includes line and piston types of transducers operated in an orientation other than those specified above.

ORIENTATIONS FOR RESPONSE AND DIRECTIVITY MEASUREMENTS

Response. The calibration measurements are made for sound propagated parallel to the positive X axis ($\phi = 0$, $\theta = 90$), unless otherwise specified on the response curve.

Directivity. The plane of the pattern is specified, and the following conventions are observed, if another orientation is not specified on the pattern:

XY Plane: The positive X axis ($\phi = 0$, $\theta = 90$) coincides with the zero-degree direction on the pattern and the positive Y axis ($\phi = 90$, $\theta = 90$) is at 90 degrees measured in a clockwise direction. Rotation is around the Z axis; the positive Z axis is directed upward from the plane of the paper.

XZ Plane: The positive X axis coincides with the zero-degree direction and the positive Z axis ($\theta = 0$) is at 90 degrees measured in a clockwise direction. Rotation is around the Y axis; the negative Y axis is directed upward from the plane of the paper.

YZ Plane: The positive Y axis coincides with the zero-degree direction and the positive Z axis is at 90 degrees measured in a clockwise direction. Rotation is around the X axis; the positive X axis is directed upward from the plane of the paper.